

OUT100



REFRIGERATION TOOL KIT FOR HFO/HFC FLUIDS

CONTENT DETAIL

Quantity	Description	Photo
1	<p>Portable thermometer delivered including:</p> <ul style="list-style-type: none"> - a digital display box with the possibility of connecting two probes -a battery for the case -two wired thermocouple type probes - a thermocouple-type contact probe 	
1	<p>Recovery station type MINIMAX E:</p> <ul style="list-style-type: none"> -Lightweight machine, equipped with an oil-free compressor -Liquid phase 90 kg/h -Steam phase 9 kg/h -Push-pull 354 kg/h - equipped with two pressure gauges (LP and HP) -pressostat HP -compatible A2L fluids 	
1	<p>Electronic Refrigerant Leak Detector</p> <ul style="list-style-type: none"> -6-segment tri-color visual leak indicator for 18 alarm levels -Sensitivity 3g/year, 7 levels. -Battery powered. 	
1	<p>REFAIRCO PK-25-SV Vacuum Pumps:</p> <ul style="list-style-type: none"> -Flow Rate: 70L/min -Final vacuum 0.02mbar -Compatible with A2L fluids -1/4 SAE fitting -50mm diameter vacuum gauge and solenoid valve -Weight 7kgs 	
1	<p>By-Pass with pressure gauges</p> <ul style="list-style-type: none"> -2-way bypass for R1234YF/R454C -High quality aluminum body with sight glass -Piston valves and PTFE seals -Pulse-free dry pressure gauges with Bourdon tube -Metal body with set screws -Supplied with robust case and charging hoses 	
1	<p>Vacuomètre</p> <ul style="list-style-type: none"> -Manomètre à aiguille diamètre 80mm sec -classe 1.6 -avec cochet de suspension 	
1	<p>Electronic Scale</p> <ul style="list-style-type: none"> -Capacity: 0 to 100 kg -resolution: 10grs -plateau 230x230mm 	